



TQC Sheen

Sag Index Applicator and Sag and Leveling Applicator

Sag Index Applicator

Manufactured by TQC Sheen, we offer a range of sag index applicators and sag and leveling applicators.

Sagging is a coating defect as the result of excessive flow on inclined or vertical surfaces. It causes uneven coating thickness with the excess of paint accumulating at the substrate edges.

The TQC Sheen Sag Index Applicator is especially designed to measure sag resistance. It features guidance plates that help you to achieve straight draw downs on glass panels and test panels.

Sag and Leveling applicator

The TQC Sheen Sag and Leveling Applicator is a special dual-function film applicator. On one side it has 10 gaps to test the tendency to sag in relation to the film thickness. On the counter side, five pairs of notches of increasing depth are made - creating two sets of film stripes. The merging of these stripes can be evaluated to define the leveling ability.

Features:

- Various sizes
- Custom options
- Calibration certificate
- Protective case
- Corrosion-resistant
- Compatible with TQC Sheen Automatic Film Applicators

Standards:

ASTM D1084, ASTM D4400, ASTM D2801

Technical Specification:

Sag Index Applicator

Material: High grade Stainless Steel

Accuracy: +/- 2 μ m

Dimensions: 18 x 18 x 120 mm

Film width: 90 mm

Wide spacing: 4.5 mm

Narrow spacing: 1.6 mm

Sag and Leveling Applicator

Material: High grade Stainless Steel

Accuracy: +/- 2 μ m

Dimensions: 15 x 28 x 100 mm

Film width: 70 mm

Ideal for:

Cosmetics, Education, Food, Inks and Coatings and Plastics and Polymers

Ordering Information:

Sag Index Film Applicators

Gap Size	Film Width 90 mm	
	Narrow spacing (1.6 mm)	Wide Spacing (4.5 mm)
50-275 μm	VF2241	VF2250
75-300 μm	VF2242	VF2251
250-475 μm	VF2243	VF2252
450-675 μm	VF2244	-
Custom μm	VF2245	VF2253



Sag Index Applicator

Sag & Leveling Film Applicators

Gap Size	Film Width 70 mm
75-300 μm	VF2246
250-475 μm	VF2247



Sag & Leveling Applicator

Accessories:

Catalog Number Article Description

VF1601 Glass Film Application Table
380x230 mm

VF1602 Glass Film Application Table
230x160 mm

VF1603 Glass Film Application Table
300x100 mm

Test charts, various options

Disclaimer

The information contained in this document is liable to modification from time to time in the light of experience and our policy of continuous product development. Check the Industrial Physics website for the latest version.

Note: We can offer bespoke sizes to meet your needs for Sag Index applicators. Please contact us directly for a quote.

Note: The total applicator width is the film width + 2 x 15 mm.

Contact Details

web. www.industrialphysics.com

email. info@industrialphysics.com