

# RO-TAP® RX-812 MODEL

Designed to be used in coarse testing applications, the affordable RX-812 coarse sieve shaker has the unique capability of using both 8 in. and 12 in. diameter test sieves, simply by using the quick-change adapters provided. The RX-812 has a quiet operation and utilizes an effective action that gives consistent accurate results. The RX-812 is recommended for use with test sieves 100 mesh and coarser.



Model	Number of Sieves	
	Full Height	Half Height
RX-812 (8 in. or 200 mm diameter)	6 sieves	13 sieves
RX-812 (12 in. or 300 mm diameter)	4 sieves	6 sieves
	4 sieves	8 sieves

Description	Part #
115v 60Hz current	RX-812
230v 60Hz current	RX-812-1
115v 50Hz current	RX-812-2
230v 50Hz current	RX-812-3

Specifications	
Oscillations per Minute	278 ± 10 (60 HZ), 231 ± 10 (50Hz)
Oscillations Displacement	1 – 1/8 in. x 7/16 in.
Dimensions	23 in. wide x 27 deep x 26 in. high (75 cm x 68 cm x 56 cm)
Weight	220 lbs. (110 kg)
Testing Applications	2 in. through US #100

All models are wired with single phase current.  
Test sieves are sold separately.